

64653 HLX

Halogen lamps with reflector MR16



Product features

- Xenon instead of krypton as the filler gas (XENOPHOT HLX versions)
- Luminous flux up to 10 % higher with same power consumption (XENOPHOT HLX versions)



Product datasheet

Technical data

Electrical data

| | |
|-----------------|----------|
| Nominal voltage | 24 V |
| Nominal wattage | 250.00 W |


Photometrical data

| | |
|-----------------------|--------|
| Nominal luminous flux | 900 lm |
|-----------------------|--------|

Light technical data

| | |
|--------------|---------|
| Focal length | 35.0 mm |
|--------------|---------|

Dimensions & weight



| | |
|----------|---------|
| Diameter | 51.0 mm |
| Length | 44.5 mm |

Lifespan

| | |
|----------|------|
| Lifespan | 50 h |
|----------|------|

Additional product data

| | |
|-----------------------------|----------|
| Base (standard designation) | GX5.3 |
| Coating | Dichroic |

Capabilities

| | |
|------------------|--------|
| Cooling | Forced |
| Burning position | hs30 |

Certificates & standards

| | |
|--------------------|---|
| EEI – Energy Label | B |
|--------------------|---|

Product datasheet

Country specific categorizations

| | |
|------------------------|-----------------|
| ANSI code | ELC |
| LIF | A1/259 |
| Order reference | 64653 HLX EL 25 |

Country specific information

| Product code | METEL code | SEG-No. | STK number | UK Org |
|---------------------|-------------------|----------------|-------------------|---------------|
| 4050300006826 | OSRH64653HLX | - | 4736553 | - |

Product datasheet



Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------|------------------------------|--------------------------------------|----------------------|--------------|
| 4050300006826 | 64653 HLX | Folding carton box 1 | 58 mm x 46 mm x 46 mm | 0.12 dm ³ | 36.70 g |
| 4050300946467 | 64653 HLX | Shipping carton box 20 | 238 mm x 119 mm x 106 mm | 3.00 dm ³ | 810.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For further technical information please refer to the following OSRAM brochure:
“Technology and applications, Low-voltage tungsten-halogen lamps”
“Halogen lamps, low and medium voltage for entertainment, technical and medical applications” cross reference list

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.