
ORIGINAL

Lamps with glass wedge bases



Product family benefits

- Wide product range
- Reliable quality


Product family features

- Original spare parts


Product family datasheet




Base




Base



Base



Base



Base

Product family datasheet

Technical data

Product description	Electrical data					Photometrical data		Dimensions & weight
	Power input	Nominal voltage	Nominal wattage	Power input tolerance	Test voltage	Luminous flux	Luminous flux tolerance	Length
921	19.4 W	12.0 V	16.00 W	±10 %	13.5 V	310 lm	±20 %	38.0 mm
921NA	19.4 W	12.8 V	16.00 W	±10 %	13.5 V	190 lm	±20 %	38.1 mm
2723	2.3 W	12.0 V	2.00 W	±8 %	13.5 V	18.6 lm	±20 %	20.0 mm
7515	25 / 6 W	12.0 V	21/5 W	±6 / ±10 %	13.5 V	440/35 lm	±15 / ±20 %	47.5 mm
7505	25 W	12.0 V	21.00 W	±6 %	13.5 V	460 lm	±15 %	47.5 mm
2821	3 W	12.0 V	3.00 W	±10 %	13.5 V	22 lm	±30 %	26.8 mm
2825	5 W	12.0 V	5.00 W	±10 %	13.5 V	50 lm	±20 %	26.8 mm
7504 ¹⁾	25 W	12.0 V	21.00 W	±6 %	13.5 V	280 lm	±20 %	47.5 mm
2827 ¹⁾	5 W	12.0 V	5.00 W	±10 %	13.5 V	30 lm	±20 %	26.8 mm
2721	1.22 W	12.0 V	1.20 W	±15 %	13.5 V	7.5 lm	±20 %	20.0 mm
2722	2 W	12.0 V	2.00 W	±15 %	13.5 V	12 lm	±20 %	20.0 mm
2820	2.2 W	12.0 V	2.00 W	±10 %	13.5 V	13.5 lm	±25 %	26.8 mm

Product description	Diameter	Lifespan		Additional product data	Certificates & standards	Country specific categorizations
		Lifespan B3	Lifespan Tc	Base (standard designation)	ECE category	Order reference
921	16.0 mm	400 h	1000 h	W2.1x9.5d	W16W	921
921NA	16.0 mm	400 h	1000 h	W2.1x9.5d	WY16W	921NA
2723	5 mm	350 h	1200 h	W2x4.6d	W2,3W	2723
7515	20.0 mm	250 / 600 h ²⁾	500 / 1600 h ²⁾	W3x16q	W21/5W	7515
7505	20.0 mm	400 h	600 h	W3x16d	W21W	7505
2821	10.3 mm	1300 h	4000 h	W2.1x9.5d	W3W	2821
2825	10.0 mm	350 h	1000 h	W2.1x9.5d	W5W	2825

Product family datasheet

Product description	Diameter	Lifespan		Additional product data	Certificates & standards	Country specific categorizations
		Lifespan B3	Lifespan Tc	Base (standard designation)	ECE category	Order reference
7504 ¹⁾	20.0 mm	400 h	600 h	WX3x16d	WY21W	7504
2827 ¹⁾	10.0 mm	350 h	1000 h	W2.1x9.5d	WY5W	2827
2721	5 mm	500 h	2000 h	W2x4.6d		2721
2722	5 mm	1300 h	4000 h	W2x4.6d	-	2722
2820	10.0 mm	600 h	4000 h	W2.1x9.5d		2820

¹⁾ Amber lamp for clear indicators

²⁾ Filament 1

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.