

COOL BLUE INTENSE

Halogen headlight lamps for cars



Areas of application

- Headlight
- Ideal for use in clear-glass headlights


Product family benefits

- Stylish look
- Up to 20 % more light (compared to standard halogen lamps)
- Bluish white light for xenon look


Product family features

- High luminous flux
- Headlight lamp for bluest legally approved halogen light
- Modern design with a silver cap (H4/H7)


Product family datasheet




Base




Base



Base



Base



Base



Base

Product family datasheet

Technical data

Product description	Electrical data				Photometrical data		Dimensions & weight	
	Power input	Nominal voltage	Nominal wattage	Test voltage	Luminous flux	Luminous flux tolerance	Length	Diameter
64150CBI	68 W ²⁾	12.0 V	55.00 W	13.2 V	1550 lm	±15 %	67.0 mm	9 mm
64151CBI	68 W ²⁾	12.0 V	55.00 W	13.2 V	1300 lm	±15 %	42.0 mm	12.0 mm
64193CBI	75 / 68 W ²⁾	12.0 V	60/55 W	13.2 V	1650/1000 lm	±12 / ±15 %	82.0 mm	17.0 mm
64210CBI	58 W ²⁾	12.0 V	55.00 W	13.2 V	1500 lm	±10 %	59.0 mm	12.0 mm
64212CBI ¹⁾	43 W ²⁾	12.0 V	35.00 W	13.2 V	800 lm	±15 %	67.0 mm	12.0 mm
64211CBI	62 W ²⁾	12.0 V	55.00 W	13.2 V	1350 lm	±10 %	67.0 mm	12.0 mm
64176CBI	19 / 64 W ²⁾	12.0 V	55/15 W	13.2 V	200/1330 lm	±10 / ±10 %	79.0 mm	13.0 mm
CBI 64219CBI	22.5 W ²⁾	12.0 V	19.00 W	13.2 V	500 lm	+10 %...15 %	67.0 mm	10.0 mm
9005CBI	73 W ²⁾	12.0 V	60.00 W	13.2 V	1700 lm	±12 %	80.3 mm	12.0 mm
9006CBI	62 W ²⁾	12.0 V	51.00 W	13.2 V	1000 lm	±15 %	80.3 mm	12.0 mm
CBI		12.0 V	55.00 W	13.2 V			75.0 mm	11.3 mm

Product description	Lifespan		Additional product data	Certificates & standards	Country specific categorizations
	Lifespan B3	Lifespan Tc	Base (standard designation)	ECE category	Order reference
64150CBI	150 h	250 h	P14.5s	H1	64150CBI
64151CBI	150 h	250 h	PK22s	H3	64151CBI
64193CBI	50 / 200 h ³⁾	100 / 400 h ³⁾	P43t	H4	64193CBI
64210CBI	100 h	200 h	PX26d	H7	64210CBI
64212CBI ¹⁾	250 h	500 h	PGJ19-1	H8	64212CBI-HCB 35
64211CBI	100 h	200 h	PGJ19-2	H11	64211CBI
64176CBI	1000 / 100 h	2000 / 200 h	PGJ23t-1	H15	64176CBI

Product family datasheet

	Lifespan		Additional product data	Certificates & standards	Country specific categorizations
Product description	Lifespan B3	Lifespan Tc	Base (standard designation)	ECE category	Order reference
CBI 64219CBI	250 h	500 h		H16	64219CBI
9005CBI	110 h	220 h	P20d	HB3	9005CBI
9006CBI	260 h	520 h	P22d	HB4	9006CBI
CBI	500 h	870 h	PX22d	HIR2	9012CBI 55W 12V

1) Lamp complies with ECE R 37 and SAE (DOT) regulations

2) Maximum

3) Filament 1

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.