

## 4000 K

LEDDriving PREMIUM | – Suitable replacement for T4W



### Areas of application

- Interior lighting

### Product benefits

- 6 year guarantee
- Perfect light distribution thanks to modern diffusor material
- Two different light colors for a variety of customization options
- Maintenance-free thanks to very long lifetime
- Up to 80 % less energy consumption (compared to standard lamps)
- Easy plug and play replacement

### Product features

- LED retrofit lamps for various applications in vehicle interiors
- LEDT4W available with color temperature: 4,000 K, 6,000 K
- LEDT4W available with light color: Warm White, Cool White
- Shockproof and vibration-proof

## Product datasheet

### Technical data



#### Electrical data

|                 |        |
|-----------------|--------|
| Nominal voltage | 24.0 V |
| Nominal wattage | 1.00 W |

#### Photometrical data

|                   |        |
|-------------------|--------|
| Color temperature | 6000 K |
| Luminous flux     | 55 lm  |

#### Dimensions & weight



|                |         |
|----------------|---------|
| Length         | 26.8 mm |
| Diameter       | 9 mm    |
| Product weight | 2.70 g  |

#### Lifespan

|             |        |
|-------------|--------|
| Lifespan B3 | 2500 h |
| Lifespan Tc | 5000 h |

#### Additional product data

|                             |      |
|-----------------------------|------|
| Base (standard designation) | BA9s |
|-----------------------------|------|

#### Certificates & standards

|              |     |
|--------------|-----|
| ECE category | T4W |
|--------------|-----|

#### Country specific categorizations

|                 |                 |
|-----------------|-----------------|
| Order reference | 3924WW-02B 1W 2 |
|-----------------|-----------------|

## Product datasheet

---

### Logistical Data

| Product code  | Product description | Packaging unit<br>(Pieces/Unit) | Dimensions (length<br>x width x height) | Volume               | Gross weight |
|---------------|---------------------|---------------------------------|-----------------------------------------|----------------------|--------------|
| 4008321875723 | 4000 K              | Blister<br>2                    | 135 mm x 95 mm x<br>13 mm               | 0.17 dm <sup>3</sup> | 17.40 g      |
| 4008321875730 | 4000 K              | Shipping carton box<br>10       | 71 mm x 104 mm x<br>146 mm              | 1.08 dm <sup>3</sup> | 122.00 g     |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### References / Links

Guarantee terms are available at

▶ [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

---

### Legal advice

Not ECE conform

Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.