
SUPER BRIGHT PREMIUM / SUPER BRIGHT – OFF-ROAD

Halogen headlight lamps for cars



Areas of application

- Headlight for off-road use
- Rally and off-road


Product benefits

- Rugged and versatile
- Excellent reliability and brightness even on the most difficult terrain


Product features

- Assortment with very high wattages and quality standards
- High-wattage off-road lamps

Product family datasheet




Product line drawing




Base




Base



Base



Base





Base



Base



Base



Base

Product family datasheet

Technical data

Product description	Electrical data					Photometrical data		Dimensions & weight
	Power input	Nominal voltage	Nominal wattage	Test voltage	Power input tolerance	Luminous flux	Luminous flux tolerance	Length
62200SBP	93 W ³⁾	12.0 V	100.00 W	13.2 V		2600 lm	±10 %	67.5 mm
62201SBP	85 W ⁴⁾	12.0 V	100.00 W	13.2 V		2300 lm	±10 %	42.0 mm
62204SBP	100 / 80 W ⁴⁾	12.0 V	100/90 W	13.2 V		2900/1700 lm	±15 / ±15 %	82.0 mm
62261SBP		12.0 V	80.00 W	13.2 V		1950 lm		59.0 mm
69005SBP		12.0 V	100.00 W	13.2 V		1700 lm		80.3 mm
69006SBP		12.0 V	80.00 W	13.2 V		1000 lm		80.3 mm
64152SB ¹⁾	93 W ⁴⁾	12.0 V	100.00 W	13.2 V		2600 lm	±12 %	67.5 mm
64153SB ²⁾	85 W ⁴⁾	12.0 V	100.00 W	13.2 V	±5 %	2300 lm	±10 %	42.0 mm
64194SB ²⁾	109 / 85 W ⁴⁾	12.0 V	100/90 W	13.2 V		2900/1500 lm	±15 / ±15 %	83.5 mm
64204SB		12.0 V	100/90 W	13.2 V				82.0 mm
64198SB	75 / 68 W ⁴⁾	12.0 V	60/55 W	13.2 V		1650/1000 lm	±12 / ±15 %	80.0 mm

Product description	Diameter	Lifespan		Additional product data	Certificates & standards	Country specific categorizations
		Lifespan B3	Lifespan Tc	Base (standard designation)	ECE category	Order reference
62200SBP	9 mm	1000 h	2000 h	P14.5s	-	62200 100W 12V
62201SBP	12.0 mm	50 h	200 h	PK22s	-	62201SBP 100W 1
62204SBP	17.0 mm	45 / 100 h	90 / 200 h	P43t	-	62204SBP 100/90
62261SBP	12.0 mm			PX26d	-	62261SBP 80W 12
69005SBP	12.0 mm			P22d	-	69005SBP
69006SBP	12.0 mm			P22d	-	69006SBP

Product family datasheet

Product description	Diameter	Lifespan		Additional product data	Certificates & standards	Country specific categorizations
		Lifespan B3	Lifespan Tc	Base (standard designation)	ECE category	Order reference
64152SB ¹⁾	9 mm			PX14.5s	-	64152SB 100W 12
64153SB ²⁾	12.0 mm	23 h		PKY22s	-	64153SB 100W 12
64194SB ²⁾	17.0 mm	45 / 85 h	85 / 170 h	PU43t	-	64194 100/80W 1
64204SB	17.0 mm			P45t	-	64204SB 100/90W
64198SB	17.0 mm	250 / 400 h	450 / 800 h	P45t	-	64198SB 60/55W1

¹⁾ 2600 lm/Not permitted on public roads. Check public law

²⁾ Not permitted on public roads. Check public law

³⁾ Approximately

⁴⁾ Maximum

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Legal advice

Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

No ECE approval

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.