

2752MF

ORIGINAL | Lamps for printed circuit boards



Areas of application

- Instrument and switch lighting

Product family benefits

- OEM Quality
- Wide product range
- Reliable quality

Product family features

- Original spare parts

Technical data


Electrical data


Power input	1.8 W
Nominal voltage	12.0 V
Nominal wattage	1.50 W
Test voltage	13.5 V
Power input tolerance	±10 %

Photometrical data

Luminous flux	6.0 lm
Luminous flux tolerance	±20 %

Dimensions & weight





Diameter	5 mm
Product weight	1.18 g
Length	21.6 mm

Colors & materials

Base color	Beige

Lifespan

Lifespan B3	1000 h
Lifespan Tc	6500 h

Additional product data

Base (standard designation)	B8.5d	
Product type (off-road vs. on-road)	On-road	
Application (Category and Product specific)	Auxiliary lamp	

Capabilities

Thickness of PCB	1.6 mm

Certificates & standards

ECE category	-
Approval marks – approval	-

Country specific categorizations

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321096760	OSRA2752MF	-	-	-

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321096760	2752MF	Unpacked 1	32 mm x 14 mm x 18 mm	0.01 dm ³	4.17 g
4008321096777	2752MF	Folding carton box 10	46 mm x 29 mm x 112 mm	0.15 dm ³	22.80 g
4008321096784	2752MF	Shipping carton box 50	148 mm x 115 mm x 55 mm	0.94 dm³	143.50 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.